


ProLoc: LUX(2.0) 32" Weatherproof Display

Never before has the world seen a weatherproof display like the Sealoc ProLoc: LUX. Tough as nails, beautifully designed and bright enough for full sunlight viewability. The ProLoc: LUX features IP65 weatherproof protection, IK10+ impact resistance and produces 2,000 NITs for a bright, clear 1080p HD picture. The ProLoc: LUX commercial display is built to withstand the harshest of conditions – rain, snow, freezing and scorching temperatures, salty-air, dusty environments, and hard impacts without failing.



With its unique, edge-to-edge glass design and sleek profile the ProLoc: LUX commercial display looks as good as it functions. It features an extra-large weatherproof media bay to house large 3rd party components. On the inside, the ProLoc: LUX utilizes Sealoc's famous and proprietary conformal coating to protect the electronics and boasts the highest quality components available (industrial-grade class A+ high TNI LCD panel, Philips LED backlighting, German-engineered cooling fans and an aircraft-grade aluminum body). The ProLoc: LUX is MET certified to the latest UL outdoor display and FCC standards to ensure years of worry free, safe operation. All packaged with an industry-best 3-year warranty with an option for 4 or 5 full years.





SEAL

sales@sealoctvs.com www.sealoctvs.com (972)525.9800

ProLoc: LUX(2.0) - PLLX322415L

32" High Bright Display

Specifications

LCD Display		
LG High TNI LCD, TFT		
Industrial / A+		
17X7		
2,000 Nits		
8Bit (16.7M colors)		
1920x1080p (HD)		
178° Vertical/Horizontal		
60Hz		
16:9		
Yes (30% - 100%)		
Yes - Pixel shift		
6ms (G to G)		
Yes		

ICD Diamland

Protection

Ingress Protection	IP65
Physical Protection	IK10+
Circuitry Protection	Conformal coating all circuits
Glass	4mm tempered, Anti- explosion retention film, Anti-reflective coating
Body Construction	Aircraft grade aluminum. HD powder coating. RAL Color Availability.
Cooling	Fans, thermostatically controlled
Operating Temperature *With optional extrem	-20°C - 50°C (-4°F - 122°F) ne cold weather heater

Power

AC Input	100-240 VAC / 50-60Hz
Max Pwr Consumption	156 Watts
Min Pwr Consumption	45 Watts
	·


Display Dimensions

Body Size (W x H x D)	771mm x 476.5mm x 118.2mm
Display Weight	28 lbs
VESA Pattern(s)	300mm x 200mm
Media Bay (W x H x D)	183mm x 73mm x 40mm

Inputs / Outputs

HDMI	Х3
RS232	X1
IR Reciever	X1
USB Power	X1
10W Marine-Grade	X2

10W Marine-Grade X2 Speakers



Sealoc Corporate

1720 Bray Central Dr., Suite 100-X McKinney, TX 75069 sales@sealoctvs.com www.sealoctvs.com (972)525.9800 Visit www.sealoctvs.com to see our complete line of outdoor televisions, digital displays, speakers, mounts, remote controls, and other accessories.



Learn more about Sealoc's custom product weatherproofing and nano-coating services. HDMI extenders/baluns, drones, receivers, gate controllers, remote controls, and much more.